

Display/Optic lamps

Concise ranges of Mains and Low Voltage tungsten Halogen lamps for the "Entertainment Industry."

Features include

- Compact design
- Excellent efficacy



Low Voltage tungsten halogen without reflector	81
Low Voltage tungsten halogen reflector	81
Mains Voltage single ended	82
Mains Voltage single ended - 3400K	82
Mains Voltage single ended - 3200K	82



Low voltage tungsten halogen without reflector

Ideal for stage and studio lighting krypton gas filling - HLX (XENOPHOT R) have Xenon gas filling

Tungsten halogen reflector lamps

Compact design with prefocussed reflector. Ideal for theatre, film and TV lighting.

Stearn ref code	type	ANSI	LIF	watt	volt	cap	sales pack
M29	64225	ESA	M29	10	6	G4	40
M30	HLX64250	ESB	M30	20	6	G4	40
M185	64260	ESA	M185	30	12	PG22	30
M130	64261		M130	30	12	G6.35	40
M134	64602		M134	50	12	G6.35	40
A1220	HLX64610	BRL	A1220	50	12	G6.35	40
M120	HLX64623	EVA	M28	100	12	GY6.35	40
A1215	HLX64625	FCR	A1215	100	12	G6.35	40
A1234	HLX64633	BRJ	A1234	150	15	G6.35	40
64650	64650			50	22.8	G6.35	40
64638	HLX64638			100	24	G6.35	40
A1216	HLX64650	FCS	A1216	150	24	G6.35	40
64647	64647			100	24	G6.35	40
M184	HLX64642	FDV	M184	150	24	GY6.35	40
64656	HLX64656	FNT		275	24	G6.35	40
M33	HLX64657	EVC	M33	250	24	G6.35	40
A1270	HLX64664			400	36	G6.35	12
A1166	HLX64665			400	36	G6.35	12



Mains Voltage tungsten halogen single ended.

Ideal for theatre, film and TV lighting.

Stearn ref code	type	ANSI	LIF	watt	volt	cap	sales pack
FSY	93591		FSY	400	240	GY9.5	24
M40	64672		M/40	500	230	GY9.5	12
A1244	64680		A1/224	500	230	GY9.5	12
P113	64540	BVM	P1/13	650	240	GY9.5	12
DYR	64686	DYR	A1/233	650	240	GY9.5	12
P115	64575	EGY	P115	1000	240	GY9.5	12



Single ended - 3400K

Suitable where colour temperature is required for 3400K sensitised material. Ideal for TV, video and film studios.

64502	64502			150	230	GX6.35	25
64505	64505			200	240	GX6.35	12
CP96	64514		CP96	300	120	GX6.35	12
P123	64515			300	240	G6.35	12
CP97	64516		C97	300	240	GX6.35	12
M38	64662		M38	300	230	GY9.5	12



MR11 35mm diameter

M119	64225			20	8	GZ4	10
M117	64617			75	12	G5.3-4.8	10
A151	64264			100	12	G5.3-4.8	10
EXR	93515			300	82	GX5.3	10
FHS	93520			300	2	GX5.3	10



Single ended - 3200K

Suitable where colour temperature is required for 3200K sensitised material. Ideal for professional film and TV recordings.

CP81	64673		CP81	300	230	GY9.5	12
------	-------	--	------	-----	-----	-------	----



MR13 42mm diameter

A1229	64607	EFM	A1229	50	8	GZ6.35	20
A1231	HLX64627	EFP	A1231	100	12	GZ6.35	20
A1271	64637		A1271	100	12	GZ6.35	20
F107	64608	EPZ		50	13.8	GX5.3	50
A1231	HLX64634	EFR	A1232	150	15	GZ6.35	20
M149	HLX64635			150	15	GZ6.35	20
EKE	93638	EKE		150	21	GX5.3	24
A1259	HLX64653	ELC		250	24	GX6.35	20
ENX	93535	ENX		360	82	GY5.3	24
FXL	93526	FXL		410	82	G6.35	24
ENH	93506	ENH		250	120	GY5.3	24
ELH	93518	ELH		300	120	GY5.3	24



MR16 50mm diameter



MR18 58mm diameter

DNF	93631	DNF		150	21	GX7.9	24
-----	-------	-----	--	-----	----	-------	----