

LED LIGHTING RGB KITS AND SINGLES



5M WARM WHITE LED STRIP IP67 R5MWWK-IP

IP67 - for interior and exterior applications

- Can be cut every 3 LEDs so the strip can be used to desired length
- Self adhesive back



REMOTE CONTROLLABLE COLOUR CHANGING LED DECKING KIT R6RGB3K

- Fully remote controllable, colour changing LEDs
- 50,000 hours average lamp life
- Suitable for walk over applications



REMOTE CONTROLLABLE 5M RGB FLEXISTRIP KIT (IP67) R5MRGBK-IP

- IP 67 - for interior and exterior applications
- Fully RGB controllable - LED colour sequence can be changed to desired colour and sequence



ADDITIONAL FITTING FOR R6RGB3K R6RGB1

- Additional fitting for R6RGB3K
- Non corrosive, die cast aluminium body, stainless steel trim
- Cool running

GARDEN SPIKES



3W LED GARDEN SPIKE / WALL WASHER R503LED

- 50 x 0.06W warm white LEDs
- 50,000 hour average lamp life
- Can be used with a spike or can be surface mounted
- Pivoting head can focus light where required



3W '2 IN 1' SPIKE AND WALL MOUNT SET (WARM WHITE) R2IN13W

- 2 in 1 design, complete with spike and wall bracket
- 3 watt high power warm white LED
- 50,000 hour average lamp life
- Integral driver



IP68 5 FITTING KIT, CIRCULAR (3 LEDs) R3LED5-01 White LEDs R3LED5-07 Blue LEDs

- Ideal for ground/deck/decorative lighting
- Each kit contains 5 miniature fittings each with 3 LEDs in either blue or white, IP44 driver, connector cables, lead & plug



9 x 1W RGB EXTERIOR WALL WASH KIT R91RGBK

Fully remote controllable, ability to pick your desired colour

- A maximum of 4 fittings can be connected together
- IP65 - suitable for interior and exterior use



3 X 1W '3 IN 1' GROUND LIGHT, WALL LIGHT, OR SPIKE FITTING R3IN13W

3 in 1 features optional ground, wall or spike use

- 3 x 1 watt warm white high power LEDs
- Suitable for walk over applications

KITS & CONNECTORS



IP68 10 FITTING KIT, CIRCULAR (3 LEDs)

R3LED10-01 White LEDs
R3LED10-07 Blue LEDs

- Ideal for ground/deck/decorative lighting
- Each kit contains 10 miniature fittings each with 3 LEDs in either blue or white, IP44 driver, connector cables, lead & plug



IP67 3 FITTING KIT, CIRCULAR (10 LEDs)

R10LED3-01 White LEDs
R10LED3-07 Blue LEDs

Suitable for walk over applications

- Each kit contains 3 lights, IP44 driver, connector cables, lead & plug, clips for mounting in decking & 3M cable
- Cool running, 50,000 hours, No UV content



2.5M RGB EXTENSION CABLE, 3 T JUNCTIONS REXTRGB

- For use with RGB range of products
- 1 additional interlinkable T junction to enable user to expand the RGB kit

ALL PRODUCTS HAVE 2 YEAR GUARANTEE!

Code	Diameter	Width	Length	Height	Depth	Max W	Cut Out	IP Rating
R5MWWK-IP		8mm	5000mm		8mm	30W		67
R5MRGBK-IP		15mm	5000mm		3mm	36W		67
R6RGB3K	60mm				67mm	12W	50mm	67
R6RGB1	60mm				67mm	12W	50mm	67
R91RGBK			270mm	60mm	125mm	9W		65
R503LED		120mm		140mm	100mm	3W		65
R3IN13W	95mm		110mm			3W		66
R2IN13W	42mm		75mm			3W		65
R3LED10-01/07 White or Blue LEDs	30mm				25mm		20mm	68
R3LED5-01/07 White or Blue LEDs	30mm				25mm		20mm	68
R10LED3-01/07 White or Blue LEDs	115mm				100mm		100mm	67
R1LED8-01/07 White or Blue LEDs	18mm				26mm	8W	13mm	65
REXTRGB			2500mm					67

DOWNLIGHTS FIRE RATED DOWNLIGHTS

ENERGY SAVING

**PART L COMPLIANT
FIRE RATED
DOWNLIGHTS**

**2 YEAR
GUARANTEE**




GU/GZ10 FIRE RATED DOWNLIGHT, DIRECTIONAL

RF208-01 White
RF208-02 Brass
RF208-03 Chrome
RF208-13 B. Chrome



12V FIRE RATED DOWNLIGHTS, STRAIGHT

RF101-01 White
RF101-02 Brass
RF101-03 Chrome
RF101-13 B. Chrome



GU/GZ10 FIRE RATED IP65 SHOWER DOWNLIGHTS

RFS10165GZ-01 White
RFS10165GZ-03 Chrome



FIRE RATED IP65 SHOWER DOWNLIGHT C/W 11W CFL LAMP

RFS1165-01 White
RFS1165-03 Chrome
RFS1165-13 B. Chrome



GU/GZ10 FIRE RATED DOWNLIGHTS, STRAIGHT

RF201-01 White
RF201-02 Brass
RF201-03 Chrome
RF201-13 B. Chrome



FIRE RATED STRAIGHT DOWNLIGHT C/W 11W GU10 CFL LAMP

RF211-01 White
RF211-03 Chrome
RF211-13 B. Chrome



12V FIRE RATED DOWNLIGHTS, DIRECTIONAL

RF108-01 White
RF108-02 Brass
RF108-03 Chrome
RF108-13 B. Chrome



12V FIRE RATED IP65 SHOWER DOWNLIGHTS

RFS10165-01 White
RFS10165-03 Chrome
RFS10165-13 B. Chrome



12V 20-60W DIMMABLE ELECTRONIC TRANSFORMER LEB60D

- C/w 150mm flying leads
- Dimmable with standard dimmers
- Integral thermal fuse to ensure safety

Code	Diameter	Width	Length	Height	Depth	Max W	Cut Out	IP Rating
RF201-01/02/03/13	80mm				135mm	50W	74mm	20
RF208-01/02/03/13	97mm				140mm	50W	85mm	20
RF211-01/03/13	86mm				135mm	11W	74mm	20
RF101-01/02/03/13	80mm				135mm	50W	74mm	20
RF108-01/02/03/13	97mm				140mm	50W	85mm	20
RFS10165GZ-01/03/13	84mm				135mm	50W	76mm	65
RFS10165-01/03/13	84mm				135mm	50W	76mm	65
RFS1165-01/03/13	97mm				135mm	11W	75mm	65
LEB60D		40mm	85mm	33mm		60W		20

SURFACE FITTINGS FLUORESCENT 2D FITTINGS



**2 X 18W 2D PL GOLF FITTING
RS218**

- C/w 2 x 4pin 18W, 4000K PL lamps
- IP65 - suitable for indoor & outdoor use
- High frequency electronic control gear
- 12,000 hour average lamp life
- Suitable for emergency conversion



**2 X 18W 2D PL GOLF FITTING EMERGENCY
RS218E**

- 3 hour emergency pack
- C/w 2 x 4pin 18W, 4000K PL lamps
- IP65 - suitable for indoor & outdoor use
- High frequency electronic control gear
- 12,000 hour average lamp life



16W 2D GOLF FITTING, C/W HF BALLAST

R162D+L-01HF White
R162D+L-02HF Brass
R162D+L-03HF Chrome

- Fully polycarbonate impact resistant body and diffuser
- C/w 4pin 2D lamp, 3500K
- IP65 - suitable for indoor & outdoor use



28W 2D GOLF FITTING, C/W HF BALLAST

R282D+L-01HF White
R282D+L-02HF Brass
R282D+L-03HF Chrome

- Fully polycarbonate impact resistant body and diffuser
- C/w 4pin 2D lamp, 3500K
- IP65 - suitable for indoor & outdoor use



**28W GOLF - 3 HR MAINTAINED EMERGENCY
R282D+LE-01 White**

- Includes white and chrome trims
- Fully polycarbonate impact resistant body and diffuser
- C/w 4pin 2D lamp, 3500K
- IP65 - suitable for indoor & outdoor use
- Ideal for corridors and stairwells



28W GOLF EYELID

R28E2D-04 Black
R28E2D-15 Satin Silver

- Fully polycarbonate impact resistant body and diffuser
- C/w 4pin 2D lamp, 3500K
- IP65 - suitable for indoor & outdoor use
- 12,000 hour average lamp life



**28W 2D PLATO FULL CIRCLE
R420CHF**

- Complete with brushed chrome & white trim
- Complete with 2D 28W 4pin colour 3500K lamp
- Energy saving high frequency electronic ballast for flicker free start
- Quick release mechanism for trim enabling easy lamp change



**28W 2D PLATO FULL CIRCLE EMERGENCY
R420CHFE**

- Complete with brushed chrome & white trim
- Complete with 2D 28W 4pin colour 3500K lamp
- Energy saving high frequency electronic ballast for flicker free start
- 3 hour emergency light



2 X 18W OUTDOOR WALL LIGHT C/W GRILLE

R218WSG-04 Black
R218WSG-15 Satin Silver

- Polycarbonate diffuser
- Die cast aluminium housing
- Corrosion resistant
- Stainless steel screws



**28W 2D UNIVERSAL EMERGENCY GEAR TRAY
R282DEPK-CU**

- Universal tray for 2D fittings
- 3 hour maintained or non-maintained
- Multi-fixing points to adapt to most 2D luminaires
- Extension brackets included for extra mounting points

Code	Diameter	Width	Length	Height	Depth	Max W	Cut Out	IP Rating
RS218	330mm				110mm	36W		65
RS218E	330mm				110mm	36W		65
R162D+L-01HF/02HF/03HF	272mm				90mm	16W		65
R282D+L-01HF/02HF/03HF	330mm				118mm	28W		65
R282D+LE-01	330mm				118mm	28W		65
R28E2D-04/15	330mm				118mm	28W		65
R420CHF	445mm				118mm	28W		20
R420CHFE	445mm				118mm	28W		20
R218WSG-04/15	266mm				105mm	2 x 18W		65
R282DEPK-CU		165mm	240mm		36mm	28W		20